



NEROLAC SURAKSHA DUST RESIST EXTERIOR EMULSION

NEROLAC

Colours that Care



PRODUCT DESCRIPTION

Nerolac Suraksha Dust Resist Exterior Emulsion is a water based exterior emulsion paint specially designed for application on exterior walls in dry or moderately humid climatic conditions. It has better dust resistance property along with rich & soft sheen.

PERFORMANCE FEATURES & BENEFITS



SURFACE PREPARATION

1. The surface to be painted must be free from all dust, grease, traces of paint flakes, algae and fungus.
2. The surface previously coated with paint must be cleaned thoroughly with a stiff wire brush to remove dirt, dust, chalking or loose flakes.
3. Wash thoroughly with water and allow to dry to ensure proper adhesion of the new paint system.
4. In case of fungus affected area, apply a liberal coat of Nerolac Fungicidal Solution.
5. Allow it to react for minimum of 6-8 h.
6. For parapet tops and other horizontal surfaces, application of 3 coats is recommended.
7. All structural cracks must be opened in V shape filled with cement and sand mixture and leakage should be stopped before actual painting.
8. Freshly plastered surfaces must be allowed to cure completely for minimum of 12 weeks.

RECOMMENDED SYSTEM FOR APPLICATION:

1. Nerolac Exterior Primer(1 coat).# Dry 4-6 h.
2. Nerolac Suraksha Dust Resist (1st coat), Dry 4-6 h.
3. Nerolac Suraksha Dust Resist (2nd coat), Dry 4-6 h.

#Nerolac Exterior Primer or self priming of Nerolac Suraksha Dust Resistant Exterior Emulsion(100% thinning).

APPLICATION

Thin 1 L paint with maximum 700-750 ml of clean water. Apply 2 to 3 coats with an interval of 4-6 h by brush or roller. Dark shade may require additional coat for hiding. For horizontal surface and Parapet tops application of 3 coats is recommended for better protection.

PRECAUTIONS

1. Refer MSDS of Suraksha Dust Resistant Exterior Emulsion for safety measures & precautions.
2. Store in well ambient conditions, ventilated locations & away from sources of ignition & fire.
3. Keep away from children.
4. In case of eye/skin contact, wash with plenty of water.
5. Inhalation/Injection is dangerous. In either case, move to fresh air & konsult medical practitioners.
6. Do not apply when ambient temperature might drop to level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Do not use universal strainers. Stir paint well before application.
10. The container must be tightly closed when not in use. Stir well and strain before use.
11. Use safety equipments like rubber or polythene gloves, safety goggles/glasses & face mask.

TECHNICAL DATA



* Practical coverage will vary according to the roughness and porosity of surface to be painted, the application method and condition, dry film and thickness and the skill of applicator.

Warranty applicable only on minimum purchase of 60 L'.

* For warranty details, please refer warranty booklet available with the dealer.

POST APPLICATION INSTRUCTIONS

For the best performance of paint, ensure proper washing and cleaning of all algae and fungal growth at regular intervals of six months.



SAFETY FEATURES

Non-Flammable



PACK SIZE

1 L, 4 L, 10 L & 20 L.



SHADE RANGE

As per Colour Scapes Fandek and shade card.



NO. OF SHADES POSSIBLE

More than 1400



SHELF LIFE

2 years from date of manufacture.

DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products, therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement, prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.