




# NEROLAC

Colours that Care

## NEROLAC IMPRESSIONS ULTRA FRESH



### PRODUCT DESCRIPTION

Nerolac Impression Ultra Fresh luxury emulsion paints your walls with an everlasting rich creme finish. Its unique paint formula captures indoor air pollutants & free formaldehyde making your air cleaner than before. With Ultra Low Odour & Ultra low VOC, this paint gives your home all-around freshness.

### PERFORMANCE FEATURES & BENEFITS

 <p>Absorbs Indoor Air Pollutants</p>	 <p>Matt Finish</p>
 <p>Formaldehyde Abatement Properties</p>	 <p>Rich Smooth Finish</p>
 <p>Ultra Low VOC &amp; Low Odour</p>	

### SURFACE PREPARATION

1. Remove all loose or Poorly adhering material, dirt, grease, wax etc. from the surface and apply a coat of Nerolac Premium or Popular Primer (Water Thinnable / Solvent Thinnable) and allow it to dry.
2. Apply Nerolac Acrylic Wall Putty / Cement Putty to level the dents, dry, followed by sanding with emery paper 180 and wipe clean.
3. Apply another coat of Nerolac Premium or Popular Primer (Water Thinnable / Solvent Thinnable) and allow it to dry. After drying sand the surface with emery paper No. 320 and wipe clean.
4. Dry minimum 8 h for solvent thinnable primer & minimum 4-6 h for water thinnable Primer.

### APPLICATION

1. Thin 1 L paint with maximum 400-500 ml of water.

2. Apply 2-3 coats of Nerolac Impressions Ultra Fresh with an interval of 4-6 h by brush or roller.

3. Dark shade may require additional coat for hiding.

### PRECAUTIONS

1. Refer MSDS for Nerolac Impressions Ultra Fresh for safety measures & precautions.
2. Store in well ambient conditions, Ventilated locations & away from sources of ignition and fire.
3. Keep away from children.
4. In case of eye / skin contact, wash with plenty of water.
5. Inhalation / Injection will cause danger. In case move to fresh air & consult a medical practitioners in both the cases.
6. Do not apply when ambient temperature might drop to a level below 10°C within 4 h of application.
7. New plaster should be allowed to cure for minimum 12 weeks.
8. Avoid extra thinning for better results.
9. Do not use universal stainers. Stir well before paint application.
10. The container must be tightly closed when not in use.

## TECHNICAL DATA



\*\*\* Actual coverage capacity may vary depending upon the method & condition of application, surface condition, temperature, wind velocity, application skills, surface roughness, surface porosity and shade.

\*\*\* Paint with estimated VOC in the range of 5g/L without addition of colorant (Ref: KNP lab results) .VOC content may vary from batch to batch.

## POST APPLICATION INSTRUCTIONS

For removing stains, Sponge clean with mild soap solution and wipe clean. Please allow 2 weeks of drying time to freshly painted wall for it to be ready for stain removal/cleaning.



### SAFETY FEATURES

Non-Flammable



### PACK SIZE

1 L, 4 L, 10 L & 20 L.



### SHADE RANGE

As per Nerolac Colour Scapes Fandeck & Shade Card



### SHELF LIFE

2 years from the date of manufacturing, when stored in the original tightly closed containers, away from direct sunlight and excessive heat



### HEALTH & SAFETY PRECAUTIONS

Avoid inhalation, eye and skin contact. In case of contact, wash with water and Seek medical attention. Do not pour the leftovers in the drain. Dispose off after natural drying



### STORAGE

Store in a cool & dry place, Keep away from direct sunlight, Thinned paint to be consumed within 24 h after thinning

## DISCLAIMER

The product information and application details given by the company has been provided in good faith and is meant to serve only as a general guideline during usage. The performance claims made are based on the tests carried out under controlled conditions and our past experience with the type of products. Therefore actual performance will depend on local factors prevailing at that point of time. Users are advised to carry-out sample tests by taking trials to ensure the suitability of products for their requirement prior to full-scale usage of our products.

The company is not liable for factors beyond its control such as application during adverse climatic conditions, use of improper application tools/techniques and surface preparation, any structural defects or the inferior quality of materials other than paints. The warranty/guarantee clauses shall accordingly be amended.